CONVEYORS MATERIAL HANDLING EQUIPMENT



Truss Conveyor

Custom built conveyors 24" - 48" widths.


Conveyors can run horizontal then transition to run on incline, (For underground storage hoppers) Each conveyor can be custom designed to your specifications and speed. 3"X3"X4" main cord 2-½" X 2-½" X 3/16" diagonals.

4646

With in-ground hoppers and Stephens Seek-N-Feed automated bin filling system, a 200 ton overhead bin can function as a 400-500 ton plant. A PLC based controller, for in-ground dump hopper and tunnel conveyor, can increase plant storage capacity and production. The system automatically fills overhead storage bins.







		(11 11 11 11
TRUSS CONVEYOR DIMENSIONS CHART						
DESCRIPTION	UNITS	A	В	C	D	CAPACITIES CU YARDS CU METERS
70 TON AGG. BIN	STD.	36'-6 7/8"	22'-1 1/4"	110'-0"	104'-8 1/16"	51.85
	METRIC	11.1482 M	6.74 M	33.528 M	31.9048 M	39.6
100 TON AGG. BIN	STD.	38'-1 3/4"	24'-0 3/4"	115'-0"	109'-5"	74.07
	METRIC	11.6272 M	7.33 M	35.052 M	33.3516 M	56.0
120 TON AGG. BIN	STD.	39'-8 5/8"	25'-0 3/4"	120'-0"	114'-2 1/8"	88.8
	METRIC	12.1063 M	7.64 M	36.576 M	34.7984 M	67.8
150 TON AGG. BIN	STD.	41'-3 7/16*	27'-1 1/4"	125'-0"	118'-10 15/16"	111.11
	METRIC	12.5853 M	8.26 M	38.1 M	36.2451 M	84.9
200 TON AGG. BIN	STD.	44'-5 3/16"	30'-3 1/4"	135'-0"	128'-4 7/8"	148.1
	METRIC	13.5433 M	9.23 M	41.148 M	39.1386 M	113.2
240 TON AGG. BIN	STD.	46'-0"	30'-10 5/8*	140'-0"	133'-1 13/16*	177.8
	METRIC	14.0224 M	9.41 M	42.672 M	40.5854 M	135.8
270 TON AGG. BIN	STD.	47'-6 7/8"	32'-10 5/8"	145'-0"	137'-10 3/4"	200
	METRIC	14.5014 M	10.02 M	44.196 M	42.0322 M	152.8
300 TEN AGG. BIN	STD.	49'-1 3/4*	34'-10 5/8"	150'-0"	142'-7 3/4"	222.2
	METRIC	14.9804 M	10.63 M	45.72 M	43.4789 M	169.7
335 TON AGG. BIN	STD.	52'-3 1/2"	37'-0 5/8"	160'-0"	152'-1 5/8"	248.1
	METRIC	15.9385 M	11.29 M	48.768 M	46.3724 M	189.5
365 TON AGG. BIN	STD.	53'-10 5/16"	39'-0 5/8"	165'-0"	156'-10 5/8"	270.4
	METRIC	16.4175 M	11.9 M	50.292 M	47.8192 M	206.5
400 TEN AGG. BIN	STD.	57'-0*	41'-0 5/8"	175'-0"	166'-4 9/16"	296.3
	METRIC	17.3756 M	12.51 M	53.34 M	50.7127 M	226.3
			NDTE: TO CONTINUALLY UPDATE AND IMPROVE OUR PRODUCT WE RESERVE THE RIGHT TO AMEND OUR STANDARD SPECIFICATIONS WITHOUT NOTICE.			


Radial Stacker

Custom built Radial Stackers 24", 30" and 36" belt widths, max length 125'.

Heavy deep frame construction 3''x3''x1/4'' main cord, $2-\frac{1}{2}''X 2-\frac{1}{2}''X 3/16''$ diagonals and heavy I beam supports and heavy rectangular structural steel axle.

Radial Stacker Conveyor

RADIAL STACKER CONVEYORS



14'-0" CLEARANCE FOR EAGLE MOBILE 15'-0" CLEARANCE FOR MUSTANG 13'-6" CLEARANCE FOR EMPIRE/STALLION/THOROUGHBRED

Screw Conveyor




Custom built with various drives and speeds; 6" - 14" Screws available with direct drives, reducer drives, and spline drives, (some sizes not available with each drive).




Weighing conveyors up to 80' long. (Designed to weigh complete batch & then start belt under full load)

Weighing Pylon



Each Shuttle is custom built to feed your bins or hoppers. 24" - 36" widths available. Rotating Shuttle Conveyors also available for multiple bin and hopper combinations or round bins.

Shuttle Conveyor



Why a Stephens?

- Owned by Stephens family since 1957
- Reputation of honest, reliable and second to none sales and service
- In-house CNC/Machine shop
- Certified in-house scales to keep load cell size
 and quantity down
- Simple and easy to service and maintain, features standard off the shelf parts
- Each plant is designed for your seismic requirements

Proud Members of





Stephens CONCRETE PLANTS • Tompkinsville, KY

Stephens Manufacturing P.O. BOX 488 • TOMPKINSVILLE , KY 42167 PHONE: 800-626-0200 • <u>OUTSIDE the USA</u> 270-487-6774 FAX: 270-487-8368 www.stephensmfg.com





Note: Parts and structure do vary from machine to machine as new product testing and research proves their success.

Local Distributor:

